

# **DHSCmi Solar induction IP camera**



I 、 This product is an outdoor surveillance camera without power connection, no wiring, simple installation and ready-to-use installation.

II、 Core selling point :

1 No electricity required: Solar and battery powered ;

2 No wiring needed: No need to thread wall, chisel a hole or destroy decoration;

3. Supported Off-line operations : Be monitored without networking ;

4 Remote viewing: WIFI network can be viewed remotely; ;

5 Human induction: Take photos immediately upon inducing people ;

6. Privacy Protection: Local storage, no leaks;

7. Induction street lamp: Sensing people at night, the lights will be automatically activated ; 8. Simple installation: self installation, no need to invite professional construction staff;

III、 Application Scope: Doorstep, Courtyard , Fishpond, Orchard, Farm, Mine, Construction site and all places where it is not convenient to receive electrical wiring.

Product Name:	Solar outdoor induction IP camera
Model:	<b>DHSCmiWIFI-2MP</b>
color:	White
Induction principle:	HMD ( Human Motion Detection )
Master chip:	Hi3516EV300 ARM926@800MHz
Sensor type:	IMX323 2.0MP 1/2.9" CMOS sensor
WIFI module:	Hi1131
WIFI agreement:	WIFI 2.4GHz , IEEE 802.11 b/g/n
Effective pixels:	2MP
Image size :	1920*1080
Focal length:	4mm ( Optional 2.8mm/6mm/8mm/12mm )
Photographic distances:	0-15meters
Shooting angle:	70°
Response time:	0.6S
Battery capacity:	4000mAh ( 2000mAh*2 )

Solar panel power:	2.2W ( Detachable, optional 3m extension cord )
Max Charge Current :	400mA
Night mode:	White light (fill light) and infrared manual switching (factory default white light mode)
White light power:	2W LED ;1W*2

Infrared power:	2W LED 1W*2	
Storage capacity:	The 32G card can be stored for about 140 days (storing about 28000 videos, According to each shooting 15 seconds, startup 200 times a day calculation), if there's no space,the earliest video would be replaced by the latest one.	The 32G card can be stored for about 45 days (storing about 9000 videos, According to each shooting 15 seconds, startup 200 times a day calculation), if there's no space,the earliest video would be replaced by the latest one.
Induction range:	0-10m	
detection angle:	120°	
Working temperature:	-10°C to 60°C	
Working humidity:	0%-90%RH	
Power supply:	Photoelectric dual-purpose, solar + built-in lithium battery power supply (optional external solar panel or power adapter)	
Stand-by power consumption:	0.0076W	0.0076W
Shooting power consumption:	Daytime≤1.2W , Night≤2.2W	Daytime≤1.4W , Night≤2.4W
IP rating:	IP67	
Accessories:	Camera* 1, Mounting bracket* 1,Screw package * 1, Warning sticker & Instructions * 1,Product qualification certificate*1	
optional accessory:	External solar panelsl、 Power adapter	
Product size:	210mm*95mm*10 0mm	
Product weight:	0.82kg	
Packing size:	256mm*205mm*1 24mm	
Packing weight:	1.27kg	
carton size:	635mm*537mm*4 30mm	
Gross weight:	27.5kg	
Case Qty:	20/box	